

**MATERIAL SAFETY DATA SHEET****24-HOUR EMERGENCY
PHONE NUMBER:
INFOTRAC 1-800-535-5053****I. PRODUCT NAME:** Extreme 1278
FLEXIBLE SEALING ADHESIVE**II. COMPOSITION**

INGREDIENTS	CONCENTRATION%	C.A.S. #	ACGIH TLV
Polyurethane oligomer	60-70	Unknown	---
N-Vinyl-2-Pyrrolisone	20-30	88-12-0	---
High Boiling Point (Meth)acrylate	10-20	5888-33-5	---
Photoinitiator	1-4	947-19-3	---
Silica Gel	1-5	112945-52-5	---

III. CHEMICAL AND PHYSICAL PROPERTIES

Vapor Pressure: 6mm Hg at 30C Vapor Density: Heavier than air
Solubility in Water: Insoluble Specific Gravity: 1.1 approx.
Boiling Point: N/A Appearance: slightly amber
Odor: mild

IV. FLAMMABILITY AND EXPLOSIVE PROPERTIES

Flash Point: >200F (P.M.C.C.)
Recommended Extinguishing Agents: Water, foam Dry Chemical or Carbon Dioxide
Hazardous Products Formed by Fire or Thermal decomposition: Toxic Fumes of Carbon and Nitrogen oxides may evolve upon exposure to Heat or Open Flame.
Unusual Fire or Explosive Hazards: None
Compressed Gases: None Solvents: None Pressure @ 23C: N.A.

V. REACTIVITY DATA

Stability: Unstable Hazardous Polymerization: May occur
Hazardous Decomposition Products: None known
Incompatibility: Oxidizers, Heat, strong mineral acids, thiosulfates

VI. SPILL OR LEAK PROCEDURES

Dike area to prevent spreading. Absorb on vermiculite, sand or other inert absorbing material. Dispose of as a chemical waste in accordance with current local state, and Federal Regulations.

VII. STORAGE AND HANDLING PROCEDURES

Storage: Avoid storage over 100 degrees F, contamination with incompatible materials.
Handling: Avoid prolonged or repeated breathing of vapor. Do not store in direct sunlight.

VIII. SHIPPING REGULATIONS

DOT and IATA Hazard Classification: Not restricted Articles
Proper DOT Shipping Name: N/A

IX. EMERGENCY TREATMENT

Eye Irritation: Immediately flush eyes with WATER for at least 15 minutes. Get immediate medical attention.

Skin Contact: Wash thoroughly with soap and water. Do not use organic solvents on skin.

Inhalation: Remove person to fresh air.

Ingestion: Get immediate medical attention.

X. PERSONAL PROTECTION

Respiratory: Use proper positive airflow ventilation in work areas.

Skin: Avoid skin contact, wear impervious gloves and protective clothing if in direct contact with material.

Disposable polyethylene gloves with vinyl latex overgloves will give protection.

Eyes: Wear chemical splash goggles or side shield safety glasses. Do not wear contact lenses.

XI. HEALTH HAZARD DATA

Hazard Categories: Immediate X Delayed X Fire ___ Pressure ___ Reactivity ___

Potential Routes of Entry: Skin X Inhalation X Ingestion X

Symptoms of Overexposure: Possible Skin and Eye irritation on contact is likely.

Exposure Limits	ACGIH	OSHA		OTHER
Ingredients:				
	Target Organs	Carcinogen		
		NTP	LARC	OSHA
	None	None	None	None

Sara Listed Ingredients: None

XII. PREPARATION INFORMATION

The information in this MSDS was obtained from current and reliable sources. However, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of the product are beyond Extreme Adhesive, Inc. Control: it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, damage or expense arising out of the product's improper use. No warranty, expressed or implied regarding the product described herein shall be created by or inferred from any statement or omissions in this MSDS. Various government agencies (e.g. DOT, EPA, FDA) may have specific regulations concerning the transportation, handling, storage use or disposal of the product, which may not be reflected in this MSDS. The user should review those regulations to ensure full compliance.

Issue date: 2/26/08