



# Material Safety Data Sheet

## 1- Chemical Product and Company Identification:

Product Name: **Extreme 1025**  
Product Type: Cyanoacrylate Ester

**24-HOUR EMERGENCY PHONE:**  
**INFOTRAC: 1-800-535-5053**

## 2- Composition/Information on Ingredients:

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>%</u>
Ethyl-2 Cyanoacrylate	7085-85-0	80-95
Poly Methyl Methacrylate	9011-14-7	5-10

<u>Exposure Limits (TWA)</u>	<u>ACGIH (TLV)</u>	<u>OSHA (PEL)</u>	<u>OTHER</u>
Ethyl-2 Cyanoacrylate	0.2 ppm	None	None

## 3- Hazards Identification:

Potential Health Effects:

Inhalation:	Exposure to vapors above the established exposure limit results in respiratory irritation, which may lead to difficulty breathing and tightness in the chest.
Skin Contact:	Bonds to skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generated heat during the cure process and, in rare instances, a large drop can burn skin.
Eye Contact:	Irritating to eyes. Causes excessive tearing. Eyelids may bond.
Ingestion:	Material is not harmful if ingested.

## 4- First Aid Measures:

Ingestion:	Ingestion is unlikely. See supplemental section for emergency action.
Inhalation:	Remove to fresh air. If symptoms persist, obtain medical attention.
Skin contact:	Soak in warm water. Do not pull skin apart. See supplemental section for emergency action.
Eye contact:	Flush with warm water. If eyelids are bonded closed, release eyelashes with water by covering the eye with a wet pad. Do not force eye open. See supplemental section for emergency action.

## **5- Fire Fighting Measures:**

Flash Point:	150-200F, Tag Closed Cup
Extinguishing Media:	Foam, Dry Chemical or Carbon Dioxide
Unusual Fire or Explosion Hazards:	None
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus.
Hazardous Combustion Products:	Trace amounts of toxic and/or irritating fumes may be released and use of breathing apparatus is recommended.

## **6-Accidental Release Measures**

Steps to be taken in case of spill or leak: Do not use clothes for clean up. Flood spilled material with water to polymerize. Cured material can be scraped up and disposed of as non-hazardous waste. Make sure spill area is well ventilated.

## **7- Handling and Storage:**

Safe storage:	Store away from heat and direct sunlight to maximize shelf life. Store inside in a dry location. Keep container tightly closed.
Handling:	Avoid contact with skin, eyes, and clothing. Avoid breathing vapor or mist. Avoid contact with paper goods or fabric. Contact with these materials may cause rapid polymerization, which can generate smoke and strong irritating vapors.

## **8- Protective Equipment:**

Ventilation:	Local exhaust ventilation recommended maintaining vapor level below exposure limits.
Respiratory protection:	Observe OSHA regulations for respirator use (29CFR 1910.134). Use NIOSH approved respirator if there is a potential to exceed exposure limits.
Skin:	Polyethylene or non-reactive gloves. Do not use cotton, PVC or nylon. See supplemental page for more information.
Eye protection:	Safety glasses or goggles with side shields.

## **9- Physical and Chemical Properties:**

Appearance:	Clear liquid
Odor:	Sharp, Irritating
Boiling Point:	Greater than 300°F
Melting Point:	Not determined
Vapor Pressure:	Less than 0.2mmHg
pH:	Not applicable
Vapor Density:	Approximately 3 (Air =1)
Evaporation rate:	Not applicable
Specific Gravity:	1.06 at 20°C
Odor Threshold:	1-2 ppm
Solubility in water:	Negligible. Polymerized by water.
Partition Coefficient:	Not determined
Volatile Organic Compound: (SCQAMD Method 316B)	< 20 g/l, <2% (estimated)

## **10- Stability and Reactivity**

Stability: Stable under recommended storage conditions.

Hazardous Polymerization: Rapid exotherm polymerization will occur in the presence of water, amines, alkalis and alcohols.

Incompatibility: Polymerized by contact with water, alcohols, amines, and alkalis.

## **11- Toxicological Information**

Acute oral LD50 >5000mg/kg (rat) (estimated). Acute dermal LD50> 2000mg/kg (rabbit) (estimated).

## **12-Ecological Information**

No Data

## **13- Disposal Considerations:**

Disposal Procedures: Dispose of in accordance with Federal, State and local regulations. Not a RCRA hazardous waste.

## **14- Transportation Information:**

### **Domestic Ground Transport:**

Proper shipping name: Combustible liquid, n.o.s. (Cyanoacrylate ester)  
Hazard class or division: Combustible liquid  
Identification number: NA 1993  
Packing Group: III

### **International Air Transportation (ICAO/IATA):**

Proper shipping name: Aviation regulation liquids, n.o.s. (Cyanoacrylate ester)  
Hazard class or division: 9  
Identification number: UN 3334  
Packing Group: None

### **Water transportation (IMO/IMDG):**

Proper shipping name: Unrestricted  
Hazard Class or Division: None  
Identification number: None  
Packing Group: None  
Marine pollutant: None

## **15- Regulatory**

TSCA 8b Inventory status: All components are listed or exempt  
CERCLA/SARA Section 302 EHS: None  
CERCLA/SARA Section 311/312: Immediate health hazard, Delayed health hazard, Fire, Reactive  
CERCLA SARA 313: None  
California Proposition 65: None  
Canada DSL/NDSL: All components are listed or exempt  
WHMIS Hazard Class: B.3, D.2.B

## 16- Other Information

<u>Hazard</u>	<u>NFPA Hazard Code®</u>	<u>HMIS Hazard Code®</u>
Health	2	2
Fire	2	2
Reactivity	2	1
Specific Hazard	No water	Personal protection: See Section 8

### First Aid Supplement

Cyanoacrylate adhesive is a very fast setting and strong adhesive. It bonds human tissue and skin in seconds. Experience has shown that accidents due to Cyanoacrylates are best handled by passive, non-surgical first aid. Treatments of specific types of accidents are suggested as follows:

**Skin Contact-** Remove excess adhesive. Soak in warm, soapy water. The adhesive will come loose from the skin in several hours. Dried adhesive does not present a health hazard even when bonded to the skin. Avoid contact with clothes, fabric, rags or tissue. Contact with these materials may cause polymerization. The polymerization of large amounts of adhesive will generate heat causing smoke, skin burns, and strong, irritating vapors. Wear rubber or polyethylene gloves and an apron when handling large amounts of adhesive.

**Skin Adhesion-** First immerse the bonded surfaces in warm, soapy water. Peel off or roll the surfaces open with the end of a blunt edge, such as a spatula or a spoon handle, then remove adhesive from the skin with soap and water. Do not try to pull the surfaces apart with a direct opposing action.

**Eyelid Adhesion-** In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in one to two days. There will be no residual damage. Do not try to open the eyes by manipulation.

**Adhesive in eye-** Adhesive introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, usually in several hours. This will cause periods of weeping until clearance is achieved. It is important to understand that disassociation will normally occur within a matter of hours, even with gross contamination.

**Mouth-** If lips are accidentally stuck together apply lots of warm water and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips with direct opposing action. It is almost impossible to swallow Cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in one to two days.

**Burns-** Cyanoacrylates give off heat on solidification. In rare cases, large drops will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of Cyanoacrylate is released from the tissue as described above.

**Surgery-** It should never be necessary to use such drastic action to separate accidentally bonded skin.

The properties represented herein are TYPICAL VALUES and not intended for use in specifications. **Extreme Adhesives, Inc.** MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE. While the information presented is believed to be accurate, no warranty or recommendation is made as to application. Determination of product suitability is the sole responsibility of the user. Suggestions made do not constitute any guarantee in as much as use conditions are beyond our control.

Revision date: 09/03/2010